



Solar Charger 200W QC3.0+PD+DC

Atuagaq nr.:





420-82



EAN:



5705730420825



Sandberg Solar Charger 200W tassaavoq seqerngup qinngorneranit toqqaannartumik innaallagissamik pilersitsisinnaasoq seqerngup qinngorneranit atuineramik qaffasissumik pitsaassusilik. Angissusaa pissutigalugu, paneli innaallagissamik naammattumik pilersitsisinnaavoq atortutit mobilit tamaasa - laptopit, powerbankit aamma innaallagissap stationit angisuut ilanngullugit. Paneli Quick Charge USB-A portimik, USB-C portimik qaffasissumik pitsaassusilimmik kiisalu DC 5521 anitsinermik peqarpoq. Paneli nalikkaanni imaluunniit seqerngup qinngorneranut sammisillugu inissillugu, standi atorlugu, tassanilu toqqaannartumik atornissaanut inissinneqarsimavoq. Atortut qajannaatsut silallu allanngorneranut akiuussinnaasut. Assartorneq ajornannginnerulersillugu katiterneqarsinnaavoq.



Paasisaqarnerugit:



www.sandberg.gl

Sandberg Solar Charger 200W QC3.0+PD+DC

Specifications

Solar panel output: 200W
Solar cell: Monocrystalline, High efficiency 22% transfer rate
Connectors:
1 x USB-A: 5V/3A (15W Max)
1 x USB-A QC 3.0: 5V/3A, 9V/2A, 12V/1.5A (18W Max)
1 x USB-C PD: 5V/3A, 9V/2A, 12V/3A, 15V/3A, 20V/3A (60W Max)
1 X DC 5521: 19.8V/10.10A (200W Max)
Dimensions (unfolded): 230.0 x 68.9 x 0.5 cm
Dimensions (folded): 51.8 x 68.9 x 4.5 cm
Weight: 8.2 kg
Operating temperature: -40? to + 65?



Emballage paasissutissat

1 Sandberg Solar Charger 200W QC3.0+PD+DC
1 Cable DC5525 – DC5525, 3m
1 Quick guide

Piaartumik ilitsersuut: <https://sandberg.gl/mt/manual/420-82>

Angissutsit

	Nioqqutissaq	Pakke
Angissuseq (cm)	68.90	57.30
Angissuseq (cm)	51.80	77.10
Itissuseq (cm)	14.00	9.30
Oqimaassuseq (g)	9,000.00	9,500.00



Nioqqutissaq:

www.sandberg.world/product/solar-charger-200w-qc30pddc

 Sandberg®

Tunisassiaq: